

## 4 Cyl Direct Port Jetting

Select the desired flowing fuel pressure, horsepower level and fuel type to determine the nitrous and fuel jet requirements i.e. if you have an 4 cylinder direct port system and you are running 10psi Flowing Fuel Pressure, with gasoline, and want a 100 HP boost you would use a 31 Nitrous and a 26 Fuel jet in each nozzle.

Spark plugs should be at least 2 steps colder than stock gapped no larger than .035. Do not use platinum tip, extended tip or any plug with multiple ground straps or split ground straps. When in doubt about heat range always go one step colder.

Ignition timing should be retarded 2 degrees per 50 hp of nitrous being sprayed.

**Check all jets for obstructions upon installation!!**

4 Cylinder Direct Port - 5psi Flowing Fuel Pressure				
HP	N20	Gasoline	Alcohol	E85
50	20	20	26	22
100	26	22	29	24
150	31	26	35	27
200	35	31	39	32
250	41	33	42	34
Call 940-767-7694 for settings above 250 HP				

4 Cylinder Direct Port - 8-10psi Flowing Fuel Pressure				
HP	N20	Gasoline	Alcohol	E85
50	20	18	20	19
100	26	20	26	22
150	31	24	31	25
200	35	26	33	27
250	41	28	38	30
Call 940-767-7694 for settings above 250 HP				

4 Cylinder Direct Port - 40-45psi Flowing Fuel Pressure				
HP	N20	Gasoline	Alcohol	E85
50	20	12	18	15
100	26	16	22	17
150	31	18	26	19
200	35	20	28	22
250	41	22	30	24
Call 940-767-7694 for settings above 250 HP				

4 Cylinder Direct Port - 55-60psi Flowing Fuel Pressure				
HP	N20	Gasoline	Alcohol	E85
50	20	N/A	17	12
100	26	14	20	15
150	31	17	25	18
200	35	19	27	21
250	41	20	29	23
Call 940-767-7694 for settings above 250 HP				

This jetting chart is for informational purposes only, NX is not responsible for misuse or misapplication.