



Read all Instructions before beginning!!!!

Caution – EXTREME DANGER – Caution

Do not use or mix any other manufacturer's products with any Nitrous Express products.

Do not use or mix any Nitrous Express products with any other manufacturer's products.

THESE INSTRUCTIONS APPLY TO NITROUS EXPRESS PRODUCTS ONLY!

FOR SANCTIONED RACE USE ONLY - NOT FOR SALE OR USE IN CALIFORNIA

Billet Bottle Bracket Instructions

PN: 11108

Assemble the brackets on the bottle with the short bracket on the bottom and the tall bracket at the top using the supplied hardware. Use the assembled bracket without the bottle mounted in the brackets as a template to locate where mounting holes should be drilled. The bottle brackets should be secured to the mounting surface of the vehicle by a minimum of grade 5 bolts and washers. Before drilling the mounting holes, be sure to check for clearance beneath the mounting surface, i.e.: fuel tank, fuel lines, and brake lines.



Mounting the Bottle

The bottle should be mounted in the trunk area or outside of the passenger compartment. If this is not possible or practical a NHRA approved blow down tube and vent fitting (PN 11708 and 11709) must be installed. The best positioning of the bottle is shown in DIAGRAM A. Mounting the bottle in this manner will allow the internal siphon tube to be covered with liquid nitrous at all times and properly supports the bottle.

DIAGRAM A

